

Specification, Terms & Conditions:-

1. SURFACE BOARD :- Teak WOOD finished with 21 mm thick, 57 to 83 mm wide and in random length in tongue and groove shapes. The edges of the boards will have a finger lock groove and the bottom side with air pass groove and treated with special anti-termite and water-resistant lacquer.

2. THE UNDER FRAME :- Made of commercial quality pine wood runners of 70 mm x 45 mm, treated with anti-termite solution and fixed on the bottom side with 10 mm thick air cushioned pads, stapled through the two wing at 330 mm x 330 mm.

3. INSTALLATION:- IPS subfloor treated with a vapor barrier to be placed on the leveled IPS sub-floor before laying the under frame. The runners having air cushion pads to be placed on the vapor barrier in perfect level at 330mm in 1 direction. The surface board to be screwed to the runner through the tongue only and will lock the screwed tongue by the groove of adjoining board. Ends of the boards will be locked by inserting the wooden fingers through the edge grooves and fixed with suitable adhesive. An expansion of 8 to 10 mm to be left open between the wooden flooring and the surrounding tiled area/walls.

4. FINISHING:- After laying the flooring, the floor boards will be leveled to a uniform surface and applied anti-skid polish on the surface.

5. Marking:- Game line marking to be carried out in required colors before applying the finish coat.

6. Warranty:- 5 Years OF MANUFACTURERS WARRANTY AGAINST

ANY PRODUCT DEFECT.

7. Work Completion period:-02 months.

8. TERMS OF PAYMENT

A. 30% at the time of material reached at sight.

B. 20% at the time of work digging and installation.

C. 20% at the time of work fitting wood boards.

D. 20% at the time of polish of wood.

E. 10% after completion of work.

9. Transportation cost included.

10. Firms are requested to submit the quotation 31/08/2019 addressed to the Principal, Shivaji Arts, Commerce & science college, Kannad, Dist. Aurangabad.